



**SECTION I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

MANUFACTURER/SUPPLIER..DCG Vision Marketing and Sales International Ltd.

ADDRESS:.....222 Worthington St. W., North Bay, ON P1B 3B4  
TELEPHONE.....1-855-639-2850  
CANUTEC (24HR).....613-996-6666  
POISON CONTROL.....800-268-9017

PRODUCT NAME.....VOC COMPLIANT SOLVENT BORNE STAMPED CONCRETE SEALER  
PRODUCT USE.....VOC COMPLIANT INDUSTRIAL SEALER  
.....FOR INDUSTRIAL USE ONLY

DATE PREPARED.....DECEMBER 14, 2014  
EFFECTIVE DATE.....JANUARY 27, 2015  
PREPARED BY.....REGULATORY DEPARTMENT AT DCG VISION MARKETING AND SALES INTERNATIONAL LTD.

**SECTION II - COMPOSITION AND INFORMATION ON INGREDIENTS**

HAZARDOUS INGREDIENT	%	CAS #	LD50 mg/kg rat	LC50 ppm rat	HRS
SOLVENT NAPHTHA (PETROLEUM) HEAVY AROMATIC	7-13	64742-94-5	8920 MG/KG	>3.8 MG/L	4
ACETONE	40-70	67-64-1	5800 MG/KG	32000 MG/KG	4
TERT-BUTYL ACETATE	10-30	540-88-5	4100 MG/KG	>2230 MG/M3	4

Refer to Section 8 for Occupational Exposure Guidelines.

**SECTION III - HAZARDS IDENTIFICATION**

**ROUTES OF ENTRY**

EYE CONTACT.....CAUSES SEVERE EYE IRRITATION.  
INGESTION.....HARMFUL, MAY ENTER LUNGS.  
INHALATION.....VAPOURS ARE IRRITATING TO RESPIRATORY TRACT. CAN CAUSE CENTRAL NERVOUS DEPRESSION.  
SKIN ABSORPTION.....CAN BE HARMFUL IF ABSORBED.  
SKIN CONTACT.....IRRITATION, REDNESS, BURNING. DRYING, AND CRACKING.  
HEALTH HAZARDS.....MATERIAL ASPIRATED INTO LUNGS MAY CAUSE INFLAMMATION AND/OR CHEMICAL PNEUMONITIS. MAY AGGRAVATE EXISTING SKIN, EYE AND LUNG CONDITIONS. CHRONIC OVEREXPOSURE MAY CAUSE IRRITATION TO RESPIRATORY TRACT, LIVER AND KIDNEY EFFECTS, CARDIAC SENSITIZATION

**SECTION IV - FIRST AID MEASURES**

**EYES** .....IMMEDIATELY FLUSH THE CONTAMINATED EYE(S) WITH LUKEWARM, GENTLY FLOWING WATER FOR 15-20 MINUTES, WHILE HOLDING THE EYELID(S) OPEN. IF A CONTACT LENS IS PRESENT, DO NOT DELAY IRRIGATION OR ATTEMPT TO REMOVE THE LENS. TAKE CARE NOT TO RINSE CONTAMINATED WATER INTO THE UNAFFECTED EYE OR ONTO THE FACE. IMMEDIATELY OBTAIN MEDICAL ATTENTION.

**INGESTION** .....NEVER GIVE ANYTHING BY MOUTH IF VICTIM IS RAPIDLY LOSING CONSCIOUSNESS, OR IS UNCONSCIOUS OR CONVULSING. DO NOT INDUCE VOMITING. HAVE VICTIM DRINK 60 TO 240 ML (2 TO 8 OZ) OF WATER. IF VOMITING OCCURS NATURALLY, HAVE VICTIM LEAN FORWARD TO REDUCE RISK OF ASPIRATION. HAVE VICTIM RINSE MOUTH WITH WATER AGAIN. IMMEDIATELY OBTAIN MEDICAL ATTENTION.

**INHALATION**.....THIS PRODUCT IS (EXTREMELY) FLAMMABLE. TAKE PROPER PRECAUTIONS (E.G. REMOVE ANY SOURCES OF IGNITION) IF BREATHING IS STOPPED, TRAINED PERSONNEL SHOULD BEGIN ARTIFICIAL RESPIRATION (AR) OR, IF THE HEART HAS STOPPED, IMMEDIATELY START CARDIOPULMONARY RESUSCITATION (CPR) OR AUTOMATED EXTERNAL DEFIBRILLATION (AED). AVOID MOUTH-TO-MOUTH CONTACT BY USING MOUTH GUARD OR SHIELDS. QUICKLY TRANSPORT VICTIM TO AN EMERGENCY CARE FACILITY.

**SKIN (DERMAL)**.....AS QUICKLY AS POSSIBLE, REMOVE CONTAMINATED CLOTHING, SHOES AND LEATHER GOODS (E.G. WATCHBANDS, BELTS). (NOTE: IT MAY BE NECESSARY TO STORE CONTAMINATED CLOTHING UNDER WATER UNTIL IT CAN BE SAFELY DECONTAMINATED OR DISCARDED. REMOVE CONTAMINATED CLOTHING, SHOES AND LEATHER GOODS (E.G. WATCHBANDS, BELTS). FLUSH WITH LUKEWARM, GENTLY FLOWING WATER FOR 5 MINUTES. IF IRRITATION PERSISTS, REPEAT FLUSHING. OBTAIN MEDICAL ADVICE. COMPLETELY DECONTAMINATE CLOTHING, SHOES AND LEATHER GOODS BEFORE REUSE OR DISCARD.

**NOTE TO PHYSICIAN** .....THE MAIN HAZARD FOLLOWING ACCIDENTAL INGESTION IS ASPIRATION OF THE LIQUID INTO THE LUNGS PRODUCING CHEMICAL PNEUMONITIS.

**SECTION V - FIRE FIGHTING MEASURES**

**FLASH POINT(°C)** ..... -18°C T.C.C. EST. (ACETONE)

**UPPER FLAMMABLE LIMIT (% BY VOL)** ..... 12.8% EST. (ACETONE)

**LOWER FLAMMABLE LIMIT (% BY VOL)** ..... 0.6% EST. (SOLVENT NAPHTHA (PETROLEUM) HEAVY AROMATIC)

**AUTOIGNITION TEMPERATURE(°C)** ..... NOT AVAILABLE

**EXTINGUISHING MEDIA** ..... DRY CHEMICAL; CARBON DIOXIDE; ALCOHOL FOAM; WATERFOG

**SPECIAL FIRE FIGHTING PROCEDURES**..... USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS OR STRUCTURES PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**. VAPOURS MAY TRAVEL ALONG GROUND AND FLASHBACK ALONG VAPOUR TRAIL MAY OCCUR NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM(EVEN EMPTY) AS PRODUCT(EVEN RESIDUE) CAN IGNITE EXPLOSIVELY ALL TWENTY LITRE PAILS AND LARGER METAL CONTAINERS INCLUDING TANK CARS & TRUCKS SHOULD BE GROUNDED AND/OR BONDED WHEN MATERIAL IS TRANSFERRED

**HAZARDOUS COMBUSTION PRODUCTS** ..... CARBON MONOXIDE AND/OR CARBON DIOXIDE AND POSSIBLY IRRITATING GASES. ACRYLIC MONOMERS.

**SECTION VI - ACCIDENTAL RELEASE MEASURES**

**SPILL** ..... VENTILATE, AVOID SKIN/EYE CONTACT; DYKE LARGE SPILLS; ABSORB ACCORDING TO GOVERNMENT REGULATIONS

**SECTION VII - HANDLING AND STORAGE**

**HANDLING & EQUIPMENT** ..... USE IN WELL VENTILATED AREA; GROUND EQUIPMENT; USE EXPLOSION PROOF TOOLS AND VENTILATION; KEEP AWAY FROM SPARKS AND OPEN FLAMES; WASH CLOTHING AND SKIN AFTER CONTACT

**STORAGE** ..... STORE IN, WELL VENTILATED AREA AT NORMAL AMBIENT TEMPERATURE

**SECTION VIII - EXPOSURE CONTROL/PERSONAL PROTECTION**

**EXPOSURE LIMITS:**

**TLV** ..... NOT AVAILABLE.

**TWA** ..... 200 PPM EST. (TERT-BUTYL ACETATE)

**ENGINEERING CONTROLS**

**EXHAUST** ..... LOCAL/MECHANICAL/EXPLOSION PROOF

**PROTECTIVE EQUIPMENT**

**GLOVES** ..... IMPERVIOUS.

**RESPIRATOR** ..... APPROVED ORGANIC CANISTER MASK OR AIR SUPPLIED

**EYE** ..... CHEMICAL SAFETY GOGGLES/GLASSES

**FOOTWEAR** ..... IMPERVIOUS

**CLOTHING** ..... IMPERVIOUS (APRON, OVERALLS)

**OTHER** ..... USE GOOD PERSONAL HYGIENE

**SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES**

**PHYSICAL STATE** ..... LIQUID

**APPEARANCE & ODOUR** ..... CLEAR, COLOURLESS; CHARACTERISTIC ODOUR

**ODOUR THRESHOLD** ..... NOT AVAILABLE

**BOILING POINT(°C)** ..... NOT AVAILABLE

**FREEZING POINT(°C)** ..... -95 to -90°C EST. (ACETONE)

**VAPOUR PRESSURE (mm Hg)** .. NOT AVAILABLE

**VAPOUR DENSITY (AIR=1)** ..... NOT AVAILABLE

**EVAPORATION RATE** ..... NOT AVAILABLE

**SPECIFIC GRAVITY** ..... 0.8700 +/- 0.01 GMS/CC

**SOLUBILITY IN WATER** ..... NOT AVAILABLE

**VOC** ..... 342 GMS/L

**COEFF. WATER/OIL DIST.** ..... NOT AVAILABLE

**SECTION X - STABILITY AND REACTIVITY**

**STABILITY** .....STABLE  
**INCOMPATIBILITY** .....STRONG ACIDS, BASES, AND OXIDIZERS. SOME FORMS OF PLASTIC, ALKALIES AND NITRATES.  
**CONDITIONS TO AVOID** .....EXCESSIVE HEAT/IGNITION SOURCES  
**HAZARDOUS DECOMPOSITION PRODUCTS**. CARBON MONOXIDE AND/OR CARBON DIOXIDE AND POSSIBLY IRRITATING GASES. ACRYLIC MONOMERS.

**SECTION XI - TOXICOLOGICAL INFORMATION**

**EFFECTS OF ACUTE EXPOSURE**

**EYES** .....CAN CAUSE SEVERE EYE IRRITATION. INCLUDING BURNING SENSATION, REDNESS, SWELLING, BLURRED VISION AND CORNEAL INJURY.  
**INGESTION** .....CAUSES IRRITATION, A BURNING SENSATION OF THE MOUTH, THROAT AND ABDOMINAL PAIN. MAY CAUSE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION, DIZZINESS, HEADACHE, DIARRHEA, NAUSEA AND VOMITING. WHEN ACCIDENTLY ASPIRATED INTO LUNGS, CAN CAUSE SEVERE INFLAMMATION.  
**INHALATION** .....EXCESSIVE INHALATION OF VAPOURS CAN CAUSE NASAL AND RESPIRATORY IRRITATION AND CENTRAL NERVOUS SYSTEM EFFECTS INCLUDING DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, BLURRED VISION AND POSSIBLE UNCONSCIOUSNESS.  
**SKIN (DERMAL)** .....INCIDENTAL CONTACT IS NON-IRRITATING. PROLONGED/REPEATED CONTACT MAY CAUSE DEFATTING OF THE SKIN WHICH CAN LEAD TO DERMATITIS. SYMPTOMS INCLUDE DRYING AND BURNING SENSATION.

**EFFECTS OF CHRONIC EXPOSURE**

**CARCINOGENICITY** ..... NOT CLASSIFIED AS CARCINOGENIC BY IARC.  
**REPRODUCTIVE** ..... EXCESSIVE EXPOSURE DURING PREGNANCY MAY BE HAZARDOUS TO THE DEVELOPING FETUS. COMPONENTS OF THIS PRODUCT ARE EMBRYOTOXIC AND FETOTOXIC IN ANIMALS AT MATERNALLY TOXIC LEVELS.  
**TERATOGENICITY** ..... MAY CAUSE TERATOGENIC/EMBRYOTOXIC EFFECTS BASED ON LAB ANIMAL STUDIES.  
**MUTAGENICITY** ..... NOT AVAILABLE  
**SYNERGISTIC PRODUCTS** ..... NOT AVAILABLE  
**OTHER** ..... EFFECTS ON THE SKIN AND EYES MAY BE DELAYED, AND DAMAGE MAY OCCUR WITHOUT THE SENSATION OR ONSET OF PAIN.

**SECTION XII - ECOLOGICAL INFORMATION**

**AQUATIC TOXICITY** .....LC50 (ONCORHYNCHUS MYKISS) 5540 MG/L EST. (ACETONE)  
LC50 (PIMEPHALES PROMELAS) 327 MG/L EST. (TERT-BUTYL ACETATE)  
**ENVIRONMENTAL FATE** .....PREVENT FROM ENTERING DRAINS, SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUNOFF OCCURS, NOTIFY AUTHORITIES AS REQUIRED.

**SECTION XIII - DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL**.....DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL PROVINCIAL AND LOCAL REGULATIONS.

**SECTION XIV - TRANSPORT INFORMATION**

**PROPER SHIPPING NAME (GROUND ONLY)** . FLAMMABLE LIQUID N.O.S. (ACETONE)  
**TDG CLASSIFICATION (GROUND ONLY)** ..... CLASS 3 UN1993 II

**SECTION XV - REGULATORY INFORMATION**

**WHMIS CLASSIFICATION/DESCRIPTION**

- B2 - FLAMMABLE LIQUID**
- D2B - TOXIC (EYE AND SKIN IRRITANT)**
- D2A - TOXIC (EMBRYOTOXIC/FETOTOXIC)**

*This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.*

**SECTION XVI - OTHER INFORMATION**

THE INFORMATION CONTAINED IN THIS FORM IS BASED ON DATA FROM SOURCES CONSIDERED TO BE RELIABLE BUT DCG VISION MARKETING AND SALES INTERNATIONAL LTD. DOES NOT GUARANTEE THE ACCURACY OR COMPLETENESS THEREOF. THE INFORMATION IS PROVIDED AS A SERVICE TO PERSONS PURCHASING OR USING THE MATERIAL TO WHICH IT REFERS AND DCG VISION MARKETING AND SALES INTERNATIONAL LTD. EXPRESSLY DISCLAIMS ALL LIABILITY FOR LOSS OR DAMAGE, INCLUDING CONSEQUENTIAL LOSS, OR FOR INJURY TO PERSONS (INCLUDING DEATH) ARISING DIRECTLY OR INDIRECTLY FROM RELIANCE UPON THE INFORMATION OR USE OF THE MATERIAL.